

Figure 1



The frame is supported by a fixed base at the bottom. A horizontal force F is applied to the right at the top-left corner. A vertical force V is applied downwards at the top-right corner. The frame is divided into three vertical bays by two internal vertical columns. The leftmost bay is labeled "Bay 1", the middle bay is labeled "Bay 2", and the rightmost bay is labeled "Bay 3".

The frame is supported by a fixed base at the bottom. A horizontal force F is applied to the right at the top-left corner. A vertical force V is applied downwards at the top-right corner. The frame is divided into three vertical bays by two internal vertical columns. The leftmost bay is labeled "Bay 1", the middle bay is labeled "Bay 2", and the rightmost bay is labeled "Bay 3".

The frame is supported by a fixed base at the bottom. A horizontal force F is applied to the right at the top-left corner. A vertical force V is applied downwards at the top-right corner. The frame is divided into three vertical bays by two internal vertical columns. The leftmost bay is labeled "Bay 1", the middle bay is labeled "Bay 2", and the rightmost bay is labeled "Bay 3".

The frame is supported by a fixed base at the bottom. A horizontal force F is applied to the right at the top-left corner. A vertical force V is applied downwards at the top-right corner. The frame is divided into three vertical bays by two internal vertical columns. The leftmost bay is labeled "Bay 1", the middle bay is labeled "Bay 2", and the rightmost bay is labeled "Bay 3".

Year	Value
2000	100
2001	105
2002	110
2003	115
2004	120
2005	125
2006	130
2007	135
2008	140
2009	145
2010	150
2011	155
2012	160
2013	165
2014	170
2015	175
2016	180
2017	185
2018	190
2019	195
2020	200

Year	Value
2000	100
2001	105
2002	110
2003	115
2004	120
2005	125
2006	130
2007	135
2008	140
2009	145
2010	150
2011	155
2012	160
2013	165
2014	170
2015	175
2016	180
2017	185
2018	190
2019	195
2020	200

